

DRIFT

 GENROSE





4"x18" Field Tile in White



4"x18" Chevron Field Tile in Blue

AVAILABLE IN:

10mm Field Tiles

Rectified Edge

4"x18" Chevron A+B Natural Finish

8"x45" Natural Finish

- All sizes are NOMINAL



White




















Grey

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 ³ / ₈ "x3" 2"x4"
			BRICKS 1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		DIAMONDS 2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
 Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" 5/8"x4"
 Diamond	4"	OCTAGONS		HEXAGONS	
 Hexagon	6"		2" w/ 0.6" Squares		1 ¹ / ₈ " 2"
 Chevron	2"x12" 6"x24"	SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ 5/8" Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"

*Other sizes available upon request



Blue

Colors shown may vary from actual product. Final selection should be made from actual product samples.



Features	Test Method	Value		
Water Absorption	ISO 10545-3	< 0.5%		
Flexion Resistance	ISO 10545-4	≥ 59 N/mm ²		
Abrasion Resistance (PEI)	ISO 10545-7	White	Grey	Blue
		IV	III	III
Thermal Shock Resistance	ISO 10545-9	Resistant		
Cracking Resistance	ISO 10545-11	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Acid Resistance	ISO 10545-13	GLA		
Alcalis Resistance		GLA		
Resistance to Cleaning Products		GA		
Resistance to Chemical Products to Pool Water		GA		
Stain Resistance	ISO 10545-14	5		
Size, Thickness, Side Straightness, Flatness, Orthogonality	-	Meets Requirements		
Hardness (Mohs)	Scratch Test (No regulated)	5		
DCOF	ANSI A137.1	0.59		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Natural Finish
- 10mm Thickness
- Rectified Edge
- PEI Rating = 3 (Blue, Grey) | 4 (White)
- V2 - Slight Shading Variation
- Frost Resistance = Yes



8"x45" Field Tile in White



www.genrose.com