

HIMALAYA

 **GENROSE**





2"x2" Mosaic in Grey
12"x24" Field Tile in White
24"x24" Field Tile in Grey

AVAILABLE IN:

10mm Field Tiles

Rectified Edge

12"x24" Matte Finish

24"x24" Matte Finish

Mosaic


















2"x2" Mosaic Matte Finish

- All sizes are NOMINAL

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

| FIELD TILES | | CUBES | | BASKETWEAVE | |
|---|---|---|--|---|---|
|  | Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum. |  | 2" 4" |  | 1 ³ / ₈ "x3" 2"x4" |
|  | |  | BRICKS 1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4" |  | DIAMONDS 2" |
| FIELD SHAPES* | | CHEVRONS | | HERRINGBONE | |
|  | Half Hexagon 6.7" Base |  | 2"x12" |  | 1"x2" 2"x4" 5/8"x4" |
|  | Diamond 4" | OCTAGONS | | HEXAGONS | |
|  | Hexagon 6" |  | 2" w/ 0.6" Squares |  | 1 ¹ / ₈ " 2" |
|  | Chevron 2"x12" 6"x24" | SQUARES | | RECTANGLES | |
|  | Trapezoid w/ Dot 4"x2 ¹ / ₂ " w/ 5/8" Dot |  | 1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3" |  | 1"x2" 1"x4" |

*Other sizes available upon request



White



Grey




Dove

Colors shown may vary from actual product. Final selection should be made from actual product samples.

2"X2" MOSAIC



White



Grey



Dove



24"x24" Field Tile in Dove

| Features | Test Method | Value |
|---|-----------------------|--------------------------|
| Water Absorption | ISO 10545-3 | ≤ 0.5% |
| Breaking Strength | ISO 10545-4 | S ≥ 1300 N |
| Modulus of Rupture | | R ≥ 35 N/mm ² |
| Impact Resistance | ISO 10545-5 | > 0.80 |
| Abrasion Resistance | ISO 10545-6 | < 175 mm ³ |
| Coefficient of Linear Thermal Expansion | ISO 10545-8 | 6.5x10 ⁻⁶ /°C |
| Thermal Shock Resistance | ISO 10545-9 | Resistant |
| Moisture Expansion | ISO 10545-10 | 0.1mm/m |
| Frost Resistance | ISO 10545-12 | Resistant |
| Resistance to Household Chemicals and Swimming Pool Salts | ISO 10545-13 | A |
| Resistance to Low Concentrations of Acids and Alkalis | | LA |
| Resistance to High Concentrations of Acids and Alkalis | | HA |
| Stain Resistance | ISO 10545-14 | 5 |
| Slip Resistance | DIN 51097 | B |
| | DIN 51130 | R10 |
| Coefficient of Friction | B.C.R.A. Rep. CEC/81 | > 0.40 Dry > 0.40 Wet |
| Dynamic Coefficient of Friction (DCOF) | ANSI DCOF A137.1-2012 | > 0.42 Wet |
| Fire Resistance | - | A1 _{fl} |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Matte Finish
- 10mm Thickness
- Rectified Edge
- PEI Rating = 5
- V3 - Moderate Variation
- Frost Resistance = Yes





www.genrose.com