

**SOAPSTONE**





30" x 60" Field Tile in Greige



30" x 60" Field Tile in Grey

# AVAILABLE IN:

## 9mm Field Tiles

Rectified Edge

12" x 12" Matte Finish

12" x 24" Matte | Half Polished | Grip Finish

## 10mm Field Tiles

Rectified Edge

18" x 36" Matte | Half Polished Finish

30" x 60" Matte | Half Polished Finish


## Mosaic

2" x 2" Mosaic Matte | Half Polished Finish

## Trim Pieces

3" x 24" Bullnose Matte Finish

3" x 30" Bullnose Half Polished Finish



- All sizes are NOMINAL

# MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE		
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 <sup>3</sup> / <sub>8</sub> " x 3" 2" x 4"	
		BRICKS		DIAMONDS		
			1" x 2" 1" x 3" 1 <sup>3</sup> / <sub>8</sub> " x 3" 2" x 4"		2"	
FIELD SHAPES*		CHEVRONS		HERRINGBONE		
	Half Hexagon	6.7" Base		2" x 12"		1" x 2" 2" x 4" 5 <sup>1</sup> / <sub>8</sub> " x 4"
	Diamond	4"				
	Hexagon	6"	OCTAGONS		HEXAGONS	
	Chevron	2" x 12" 6" x 24"		2" w/ 0.6" Squares		1 <sup>1</sup> / <sub>8</sub> " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES		
	4" x 2 <sup>1</sup> / <sub>2</sub> " w/ 5 <sup>1</sup> / <sub>8</sub> " Dot		1" x 1" 1 <sup>3</sup> / <sub>8</sub> " x 1 <sup>3</sup> / <sub>8</sub> "	2" x 2" 3" x 3"		1" x 2" 1" x 4"

\*Other sizes available upon request



White



Grey



Black



Greige



Green

Colors shown may vary from actual product. Final selection should be made from actual product samples. Products and availability are subject to change, please refer to our website for the most up to date selection.

## 2"X2" MOSAIC



30" x 60" Field Tile in Green

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.6% / ± 2mm
Thickness		± 5% / ± 0.5mm
Straightness of Sides		± 0.5% / ± 1.5mm
Rectangularity		± 0.5% / ± 2mm
Surface Flatness		± 0.5% / ± 2mm
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	35 N/mm <sup>2</sup> min.
Breaking Strength		1300 N min.
Abrasion Resistance	ISO 10545-6	175 mm <sup>3</sup> max.
Frost Resistance	ISO 10545-12	Required
Chemical Resistance	ISO 10545-13	min. UB
Dynamic Coefficient of Friction (DCOF)	ANSI A137.1	Matte/Grip - WET: > 0.42
Recycled Content	-	> 30%

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Disclaimer:** DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

**Product Info:**

- Through Body Porcelain Tile
- Matte | Half Polished | Grip Finish
- 9mm | 10mm Thickness
- Rectified Edge
- PEI Rating = 5
- V3 - Moderate Variation
- Frost Resistance = Yes





[www.genrose.com](http://www.genrose.com)