

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.5%
Thickness		± 5%
Wedging		± 0.6%
Warpage		± 0.5%
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	R ≥ 35 N/mm <sup>2</sup>
Deep Abrasion Resistance	ISO 10545-6	123 mm <sup>3</sup>
Coefficient of Linear Thermal Expansion	ISO 10545-8	9x10 <sup>-5</sup> xC <sup>-1</sup>
Thermal Shock Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Min. B
Stain Resistance	ISO 10545-14	Min. Class 3
Slip Resistance	DCOF (Wet)	≥ 0.5
	DIN 51130 R	R10

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte Finish
- 9mm Thickness
- Rectified | Pressed Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes


[www.genrose.com](http://www.genrose.com)