




Features	Test Method	Value	
Length and width	ISO 10545 - 2	± 0.2 %	
Thickness		± 5 %	
Linearity		± 0.2 %	
Wedging		± 0.2 %	
Warpage		± 0.2 %	
Water Absorption	ISO 10545 - 3	< 0.1%	
Modulus of Rupture	ISO 10545 - 4	45 N/mm <sup>2</sup>	
Breaking Strength		2500 N (9 mm)	
Scratch Resistance	ISO 10545 - 6	Average < 150 mm <sup>3</sup>	
Thermal Expansion Coefficient	ISO 10545 - 8	6.8 MK <sup>-1</sup>	
Thermal Shock Resistance	ISO 10545 - 9	Resistant	
Frost Resistance	ISO 10545 - 12	Resistant	
Chemical Resistance	ISO 10545 - 13	Household	Acids and Alkali
		UA	Resistant
Stain Resistance	ISO 10545 - 14	Resistant	
DCOF (WET)	ANSI A326.3	0.75	
  <p style="text-align: center;">This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p> 			

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Through Body Porcelain Tile
- Natural Finish
- 9mm Thickness
- Rectified Edge
- PEI Rating = 4
- V2 - Slight Shading Variation
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)