

Features	Test Method	Value	
Water Absorption	ASTM C373	≤ 20%	
Scratch Hardness	MOHS	Wall Tile	Wall Deco
		2.0	4.0
Breaking Strength	ASTM C648	≥ 125 lbs	
Chemical Resistance	ASTM C650	Class A - E	
Frost Resistance	ASTM C1026	Not Resistant	
Stain Resistance	ASTM C1378	Class A	
DCOF (WET)	ANSI A137.1 ANSI A326.3	< 0.42	
Indoor Environmental Quality	-	No VOCs Emission	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Specialty Product Disclaimer:

This is a finely decorative Specialty Product series with metallic or distinctive glazing finishes. These tiles are subject to surface damage when exposed to physical or chemical forces.

Special Cleaning Instructions:

These tiles have a special decorative finish with precious metals or distinctive glazing, and therefore should be cleaned only with a cloth soaked in water and neutral detergent. Do not use acidic or abrasive cleaning products or sponges that may damage the tile surface.

Product Info:

- Ceramic Tile
- Matte | Glossy Finishes
- 7mm Thickness
- Pressed Edge
- V1 - Uniform Appearance
- Frost Resistance = No

