

Features	Test Method	Value	
Length / Width	EN ISO 10545 - 2	± 0.25%	
Thickness		± 2.5%	
Straightness of Side		± 0.15%	
Rectangularity		± 0.4%	
Surface Flatness		± 0.2%	
Water Absorption		EN ISO 10545 - 3	15% to 17%
Weight / M <sup>2</sup>	-	<b>8mm Thick</b>	<b>10mm Thick</b>
		14.85 kg	17.78 kg
Modulus of Rupture	EN ISO 10545 - 4	≥ 25 N / mm <sup>2</sup>	
Thermal Shock	EN ISO 10545 - 9	Pass	
Frost Resistance	EN ISO 10545 - 12	Not Suitable	
Chemical Resistance	EN ISO 10545 - 13	Class A - B	
Stain Resistance	EN ISO 10545 - 14	Class 3	
Fire Rating	-	Class A1 Non Combustible	
Recycled Content	-	Up to 20%	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



**Installation Note:**

- Use .5"x8" Finishing Strip with straight bond installation.

**Product Info:**

- Ceramic Tile
- Gloss Finish
- 8mm | 10mm Thicknesses
- V1 - Uniform Appearance - (6"x16" Wall | 6"x16" Beveled Wall | Finishing Strip)
- V2 - Slight Shade Variation - (Flat Liner)
- Frost Resistance = No



[www.genrose.com](http://www.genrose.com)