

Features	Test Method	Value		
		7 cm ≤ N < 15 cm	N ≥ 15 cm	
Sides	ISO 10545-2	mm	%	mm
		± 0.4	± 0.3	± 1.0
Thickness	ISO 10545-2	± 0.5	± 5.0	± 0.5
Straightness of Sides	ISO 10545-2	± 0.4	± 0.3	± 0.8
Rectangularity	ISO 10545-2	± 0.4	± 0.3	± 1.5
Surface Flatness	ISO 10545-2	± 0.6	± 0.4	± 1.8
Water Absorption	ISO 10545-3	≤ 0.1%		
Flexion Resistance	ISO 10545-4	S ≥ 700 N < 7.5 mm S ≥ 1300 N ≥ 7.5 mm R ≥ 35 N/mm ²		
Impact Resistance	ISO 10545-5	> 0.80		
Coefficient of Linear Thermal - Expansion - Linearer	ISO 10545-8	6,7×10 ⁻⁶ /C°		
Resistance to Thermal Shocks	ISO 10545-9	Resistant		
Moisture Expansion (in mm/m)	ISO 10545-10	MAX 0.1 mm/m		
Frost Resistance	ISO 10545-12	Resistant		
Chemical Resistance	ISO 10545-12	Household - B Min		



This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Brushed Finish
- 9mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes



www.genrose.com