

Features	Test Method	Value
Dimensional Features	ISO 10545-2	138 mm +/- 0,6 % x 138 mm +/- 0,6 % 138 mm +/- 0,6 % x 239,5 mm +/- 0,6 %
Water Absorption	ISO 10545-3	$E_b \leq 0,5\%$
Modulus Of Rupture And Breaking Strength	ISO 10545-4	Minimum 35 N/mm ² Individual Minimum 32 N/mm ²
Abrasive Resistance	ISO 10545-7	PEI 3: Grey, Indigo & Washed Blue PEI 4: White
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-11	Resistant
Household Products Resistance	ISO 10545-13	GA
Chemical Resistance	ISO 10545-13	GHA
Stain Resistance	ISO 10545-14	>3
Non-Slip Value	DIN 51130:2014 ANSI A137.1	R10 / CLASS 2 DCOF >0,42

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Matte Finish
- 8.5mm Thickness
- Pressed Edge
- PEI Rating = 3 (Other Colors) | 4 (White)
- V2 - Slight Shading Variation
- Frost Resistance = Yes

