

Features	Test Method	Value
Water Absorption	C373	≤ 0.1%
Thickness Dimension	C499	≤ ± 0.04 in
Facial Dimension	C499	≤ ± 0.25%
Warpage Average	C485	≤ ± 0.40%
Wedging Average	C502	≤ ± 0.25%
Bond Strength	C482	≥ 200 psi
Breaking Strength	C648	≥ 400 lbf
Hardness (Mohs)	-	≥ 7
Visible Abrasion Resistance for Glaze Tile	C1027	Class 4
Frost Resistance	C1026	Resistant
Chemical Resistance	C650	Class A
Stain Resistance	C1378	Class A*
DCOF (WET)	-	≥ 0.52 (Honed)*







This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

\*Values given are for honed material. No values are given for polished material.

**The polished finish is not recommended on the floor in areas subject to exposure for grease, oil or water.**

**Product Info:**

- Glazed Porcelain Tile
- Honed | Polished Finishes
- 8mm | 6mm Thicknesses
- Rectified Edge
- PEI Rating = 4
- V2 - Slight Shading Variation
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)