

Features	Test Method	Value	
		Polished	Matte
Length and Width	ISO 10545-2	± 0.5% ± 2mm	± 0.5% ± 2mm
Thickness		± 0.5% ± 2mm	± 0.5% ± 2mm
Straightness of Sides		± 5% ± 0.6mm	± 5% ± 0.5mm
Rectangularity		± 0.3% ± 1.5mm	± 0.3% ± 1.5mm
Surface Flatness		± 0.3% ± 1.5mm	± 0.3% ± 1.5mm
	ASTM C 485	Warpage Diagonal/Edge ±0.4%	
Water Absorption	ISO 10545-3	≤ 0.1% Bla GL	
Bending Strength	ISO 10545-4	≥ 35 N/mm <sup>2</sup>	
Abrasion Resistance	ISO 10545-7	Class 3 (Fossena, Black Mirror) Class 4 (Colorado, Daino)	
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Class A	
Acid and Base Resistance		Class LA	Class LA - HA
Stain Resistance	ISO 10545-14	Class 5	
Scratch Hardness (Mohs)	EN 101	> 6	
Slip Resistance	DIN 51097	-	Class B
	DIN 51130	-	R10
	B.C.R.A. REP. CEC. 6/81	-	0.40 ≤ μ ≤ 0.74
	DCOF ACU TEST	-	WET > 0.42

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Glazed Porcelain Tile
- Matte | Polished Finish
- 10mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes


[www.genrose.com](http://www.genrose.com)