

Features	Test Method	Value
Reaction To Fire	Decision 96/603/EEC amended	Class A1-A1fl
Water Absorption	ISO 10545-3	E > 0.5%
Breaking Strength	ISO 10545-4	≥ 1100 N
Adhesion with Cement Adhesive Type	-	Class C1: ≥ 1 N/mm ²
Slip Resistance*	-	(Exterior) ≥ Class 2 and/or ≥ R10 (Interior) Class 1 and/or R9
Thermal Shock Resistance	-	Resistant
External Use - Freeze-Thaw Resistance	ISO 10545-12	Resistant
Internal Use	-	All Colors and Finishes Comply
This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.		

*Slip Resistances value is for White Matte only. All other colors and finishes have No Performance Declared

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info for White:

- Glazed Porcelain Tile = Glossy Finish
- Color Body Porcelain Tile = Matte | Silk Finishes
- Matte | Glossy | Silk Finishes
- 8.2mm Thickness
- Pressed Edge
- PEI Rating = 5 (Matte Finish)
4 (Glossy | Silk Finishes)
- V3 - Moderate Variation
- Frost Resistance = Yes

Product Info for Blanco:

- Glazed Porcelain Tile = Glossy Finish
- Color Body Porcelain Tile = Matte Finish
- Matte | Glossy Finishes
- 8.2mm Thickness
- Pressed Edge
- PEI Rating = 5 (Matte Finish)
4 (Glossy Finish)
- V3 - Moderate Variation
- Frost Resistance = Yes

Product Info for Grigio | Onix Gris:

- Glazed Porcelain Tile
- Matte Finish
- 8.2mm Thickness
- Pressed Edge
- PEI Rating = 5
- V3 - Moderate Variation
- Frost Resistance = Yes

Features	Test Method	Value
Reaction To Fire	Decision 96/603/EEC amended	Class A1
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	≥ 600 N
Adhesion with Cement Adhesive Type	-	Class C1: ≥ 0.5 N/mm ²
This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info For Wall Tiles:

- Ceramic Tile
- Glossy Finish
- 8.2mm Thickness
- Pressed Edge
- V3 - Moderate Variation
- Frost Resistance = No

