

Features	Test Method	Value
Thickness	ISO 10545-2	± 5%
Surface Flatness	ISO 10545-2	± 0.35%
Surface Quality	ISO 10545-2	Conforms 95% of the tiles are free from visible flaws
Water Absorption	ISO 10545-3	Avg. 0.08%
Bending Strength	ISO 10545-4	53 N/mm ²
Coefficient of Restitution	ISO 10545-5	0.91 No surface damage
Breaking Strength	ASTM C170M-16	5000 N
Resistance to Deep Abrasion	ISO 10545-6	Avg. 140 mm ³
Thermal Shock Resistance	ISO-10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance (Low Concentration)	ISO 10545-13	ULA-ULB (Matte) ULB (Polished)
Chemical Resistance (Domestic)	ISO 10545-13	UA
Fungal Resistance	ASTM-G-21-5	Resistant
Resistance to Staining	ISO 10545-14	Class 5 (Matte) Class 3-4 (Polished)
DCOF (WET)	ANSI A326.3 2021	≥ 0.42 (Matte)





This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Disclaimer: DCOF wet and dry is different on every production lot and can vary. This number represents the average DCOF of the tested production lots. If the spec listed is over the minimum standard, it will meet the requirement.

Installation: See website for installation tips.

Product Info:

- Color Body Porcelain Slabs
- Matte | Polished Finishes
- 12mm Thickness
- Non-Rectified Edge
- Frost Resistance = Yes



www.genrose.com