

Features	Test Method	Value		
		N < 7cm	7cm ≤ N < 15cm	N ≥ 15cm
Length and Width	ISO 10545-2	± 0.5mm	± 0.9mm	± 0.6mm ± 2mm
Thickness		± 0.5mm	± 0.5mm	± 0.5mm ± 0.5mm
Straightness of Sides		N/A	± 0.75mm	± 0.5mm ± 1.5mm
Squareness		N/A	± 0.75mm	± 0.5mm ± 2mm
Planarity		N/A	± 0.75mm	± 0.5mm ± 2mm
Water Absorption	ISO 10545-3	< 0.2%		
Bending Strength	ISO 10545-4	> 40 N/mm <sup>2</sup>		
Deep Abrasion Resistance	ISO 10545-6	≤ 175 mm <sup>3</sup>		
Frost Resistance	ISO 10545-12	Resistant		
Resistance to Low/High Concentrations of Alkalis and Acids	ISO 10545-13	Low: LA		
Resistance to Household Chemical Products and Swimming Pool Additives		High: HA		
Stain Resistance	ISO 10545-14	A		
Stain Resistance	ISO 10545-14	Class 5		
Hardness in Mohs Degrees	UNI EN 101	5		
Slip Resistance (Coefficient of Friction)	DCOF	> 0.42		
Recycled Content	-	52%		
This product will contribute to GBC Italia registered LEED projects.				

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



**Product Info:**

- Glazed Porcelain Tile
- Matte | Polished Finish
- 9.5mm Thickness
- Pressed Edge
- PEI Rating = 5 (White | Light Grey), 3 (Blu | Emerald | Black)
- V1 - Uniform Appearance | V2 - Slight Shading Variation
- Frost Resistance = Yes

