

Features	Norms	Fixed Value
<b>Water Absorption</b>	UNE EN ISO 10545 Part 3	E<0.5%
<b>Bending Strength</b>	UNE EN ISO 10545 Part 4	>35 N/mm <sup>2</sup>
<b>Thermal Shock Resistance</b>	UNE EN ISO 10545 Part 9	Resists Test
<b>Cracking Resistance</b>	UNE EN ISO 10545 Part 11	
<b>Frost Resistance</b>	UNE EN ISO 10545 Part 12	
<b>Surface Abrasion Resistance</b>	UNE EN ISO 10545 Part 7	3
<b>Scratch Resistance</b>	UNE EN ISO 10545 Part 8	6
<b>Anti-Slip</b>	UNE ENV 12633:2003	Class 1

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

### Hygienic and Safe Surfaces with ACTIV

A new anti-bacterial technology for ceramic tiles with a true silver ion shield incorporated into the product prior to firing. The treatment is an integral part rather than a layer applied to the surface, that eliminates up to 99.9% of bacteria and other harmful microorganisms, reducing the possibility of contagion.

- 24 hr/day protection
- Easier cleaning
- Eliminates odors and reduces stains
- Guarantees constant antimicrobial and antibacterial action (under any light conditions)
- Exceptional durability
- Inhibits growth of pathogenic microorganisms forever
- Contributes to a healthier environment
- Ideal for residential and commercial areas:  
 kitchens, bars, restaurants, catering establishments, canteens, medical buildings, schools, offices, bathrooms, spas, swimming pools, and gyms

### Product Info:

- Glazed Porcelain Tile
- Matte Finish
- 10mm Thickness
- Pressed Edge
- PEI Rating = 4 (Venato) | 3 (Other Colors)
- Frost Resistance = Yes
- V3 - Moderate variation is inherent in this tile

