

| Features | Test Method | Value | |
|-------------------------------|-----------------------|---|-------------------|
| Water Absorption | ISO 10545-3 | ≤ 0.5% | |
| Bending Strength | ISO 10545-4 | ≥ 35 N/mm ² | |
| Breaking Strength | ISO 10545-4 | Thickness ≤ 7,5 mm | ≥ 700 N |
| | | Thickness ≥ 7,5 mm | ≥ 1300 N |
| | ASTM C 648 | Average ≥ 250 lbf Individual ≥ 225 lbf | |
| Resistance to Abrasion | ISO 10545-7 | from 2 to 5 according to color | |
| Chemical Agent Resistance | ASTM C 650 | Class A | |
| Resistance of Chemical Attack | ISO 10545-13 | Domestic Chemicals | Low Concentration |
| | | GA | GLA |
| Stain Resistance | ISO 10545-14 | ≥ Class 3 | |
| | ASTM C 1378 | Class A | |
| Slip Resistance | ANSI A137.1-2012 DCOF | > 0.42 | |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Matte Finish
- 9.5mm Thickness
- Pressed Edge
- PEI Rating = 3 (Nero) | 4 (All Other Colors)
- V3 - Moderate Variation
- Frost Resistance = Yes

