

Features	Test Method	Value
<b>Dimensions and Surface Quality</b>	ISO 10545-2	Compliant
<b>Water Absorption</b>	ISO 10545-3	≤ 0.5%
<b>Breaking Strength</b>	ISO 10545-4	1600 - 2400 N
<b>Modulus of Rupture</b>	ISO 10545-4	35 – 45 N/mm <sup>2</sup>
<b>Thermal Resistance</b>	ISO 10545-9	Resistant
<b>Crazing Resistance</b>	ISO 10545-11	Resistant
<b>Frost Resistance</b>	ISO 10545-12	Resistant
<b>Chemical Resistance</b>	ISO 10545-13	Class A – Resistant
<b>Stain Resistance</b>	-	Class 5
<b>Slip Resistance</b>	UNE 41901	Class 1
<b>Recycled Material</b>	-	≥ 30%
<p>This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



**Product Info:**

- Glazed Porcelain Tile
- 9mm Thickness
- Matte Finish
- Rectified Edge
- PEI Rating = 3 (Encina) | 4 (Other Colors)
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)