



Features	Test Method	Value
Length and Width	ISO 10545-2	+ / - 0.5%
Thickness		+ / - 0.5%
Straightness of Sides		+ / - 0.5%
Rectangularity		+ / - 0.5%
Water Absorption	ISO 10545-3	>10%
Breaking Strength	ISO 10545-4	>1000
Resistance to Surface Abrasion	ISO 10545-8	PEI 2
Thermal Shock Resistance	ISO 10545-11	Guaranteed
Chemical Resistance (Domestic)	ISO 10545-14	GB
Chemical Resistance (High Concentration)		GLB
Recycled Material	-	48%
VOC Emissions	-	No
  <p style="text-align: center;">This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Ceramic Wall Tile
- Glossy | Crackle Finishes
- 10mm Thickness
- Pressed Edge
- Frost Resistance = No
- V3 - Moderate Variation



www.genrose.com