



Features	Test Method	Value	
		Matte	Polished
Thickness		9mm – 0.35″	9mm – 0.35"
Water Absorption	ISO 10545-3 ASTM C-373	≤ 0.5%	≤ 0.5%
Deep Abrasion	ISO 10545-7 ASTM C-1027	136	135
Scratch Hardness		9	6
Breaking Strength	ISO 10545-4	≥ 450	≥ 450
	ASTM C648	≥ 500	≥ 450
Frost Resistance	ISO 10545-12	Resistant	Resistant
Chemical Resistance	ISO 10545-13	Class A - Res.	Class A - Res.
Stain Resistance	ISO 10545-14	Class 5	Class 5
	ASTM C1378	Class A	Class A
DCOF (Wet)	ANSI B101.3	> 0.42	< 0.42

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info for Charcoal I Warm White I Smoke I Mica:

- Unglazed Porcelain Tile
- Matte | Polished Finishes
- 9mm Thickness
- Rectified Edge
- V1 Uniform Appearance
- Frost Resistance = Yes



SUPREMEGlazed Porcelain Tile

Features	Test Method	Value	
		Matte	Polished
Thickness	All Other Tiles	9mm – 0.35"	9mm – 0.35"
	24"x48" Field Tile	9.5mm – 0.37"	9.5mm – 0.37"
Water Absorption	ISO 10545-3 ASTM C-373	≤ 0.5%	≤ 0.5%
Abrasion Resistance	ISO 10545-7 ASTM C1027	4	4
Scratch Hardness	All Other Tiles	9	6
	12"x12" Field Tile	5	5
Breaking Strength	ISO 10545-4 ASTM C648	≥ 450	≥ 450
Frost Resistance	ISO 10545-12 ASTM C1026	Resistant	Resistant
Chemical Resistance	ISO 10545-13 ASTM C650	Class A - Res.	Class A - Res.
Stain Resistance	ISO 10545-14	Class 5	Class 5
	ASTM C1378	Class A	Class A
DCOF (Wet)	ANSI B101.3 & A137.1-2017	≥ 0.42	< 0.42

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info for True White:

- Glazed Porcelain Tile
- Matte | Polished Finishes
- 9mm | 9.5mm Thickness
- Rectified Edge
- PEI Rating = 4
- V1 Uniform Appearance
- Frost Resistance = Yes



www.genrose.com