

Features	Test Method	Value	
Surface Quality	ISO 10545-2	Min. 95% of tiles without defects	
Water Absorption	ISO 10545-3	≤ 0.5	
Bending Strength	ISO 10545-4	> 52 N/mm ²	
Breaking Strength	ISO 10545-4	> 2500 N	
Deep Abrasion Resistance	ISO 10545-6	<109 mm ³	
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	Low Concentration	Domestic Chemicals
		GLA/GHA	GA
Stain Resistance	ISO 10545-14	Class 5	
Slip Resistance	UNE ENV 12633	Class 1 Natural Class 3 Antislip	
Critical Angle of Slip	DIN 51130	R9 Natural R11 Antislip	
Reaction to Fire Test	UNE EN 13501-1:2002	A1 / A1FL	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide.

Product Info:

- Color Body Porcelain Tile
- Matte | Anti-Slip Finishes
- 6mm | 9mm | 20mm Thicknesses
- Rectified Edge
- PEI Rating = 3 - Anthracite
4 - Sand | Grey | Dark Grey
- Frost Resistance = Yes
- V2 - Slight Shading Variation

