

| Features | Test Method | Value | |
|---|----------------------|-----------------------------------|---|
| | | Porcelain | Porcelain 2 CM |
| Water Absorption | ISO 10545-3 | ~ 0.1% | ~ 0.1% |
| Bending Strength | ISO 10545-4 | ~ 50 N/mm ² | ~ 50 N/mm ² |
| Frost Resistance | ISO 10545-12 | Frost Proof | Resistant |
| Thermal Shock Resistance | ISO 10545-9 | Resistant | Resistant |
| Color Resistance to Light Exposure | DIN 51094 | Resistant | Resistant |
| Breakage Load | EN 12825 | - | Class 1 24"x48" / 16"x48" / 12"x48" 32"x32" / 16"x48" Class 1 ~7,00 kN center 24"x36" / 24"x24" Class 2 ~8,00 kN center 16"x16" Class 4 ~10,00 kN center 8"x18" |
| Mechanical Strength | EN 1339-F | - | U11 24"x36" / 24"x24" 16"x16" U14 8"x18" |
| Skid Resistance | ANSI 137.1-2012 DCOF | > 0.42 Natural & Grip Surfaces | ≥0.60 |
| Resistance of Chemical Attack | ISO 10545-13 | GB Minimum | GA |
| Stain Resistance | ISO 10545-14 | Class 3 | Class 3 |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Through Body Porcelain Tile
- Matte Finish
- 8.5mm | 20mm Thicknesses
- Rectified | Natural Edge
- V3 - Slight Shading Variation
- Frost Resistance = Yes


www.genrose.com