

Features	Test Method	Value	
		Matte	Polished
<b>Length And Width</b>	ISO 10545-2	±0.5%	±0.5%
<b>Thickness</b>	ISO 10545-2	±5%	±5%
<b>Wedging</b>	ISO 10545-2	±0.6%	±0.6%
<b>Warpage</b>	ISO 10545-2	±0.5%	±0.5%
<b>Water Absorption</b>	ISO 10545-3	≤ 0.5%	≤ 0.5%
<b>Bending Strength</b>	ISO 10545-4	≥ 35 N/MM <sup>2</sup>	≥ 35 N/MM <sup>2</sup>
<b>Resistance to Deep Abrasion</b>	ISO 10545-6	<175 mm <sup>3</sup>	-
<b>Coefficient of Linear Thermal Shocks</b>	ISO 10545-8	9x10 <sup>-5</sup> C-1	9x10 <sup>-5</sup> C-1
<b>Thermal Shock Resistance</b>	ISO 10545-9	Resistant	Resistant
<b>Crazing Resistance</b>	ISO 10545-11	Resistant	Resistant
<b>Frost Resistance</b>	ISO 10545-12	Resistant	Resistant
<b>Chemical Resistance</b>	ISO 10545-13	Min. GB	Min. GB
<b>Stain Resistance</b>	ISO 10545-14	Min. Class 3	Min. Class 3
<b>Slip Resistance</b>	BOT 3000 WET DCOF	> 0.42	-
	DIN 51130 R	R9	-

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Glazed Color Body Porcelain Tile
- Matte | Polished Finishes
- 9.5mm Thickness
- Rectified Edge
- PEI Rating = 5 (Polished)
- V2 - Slight Shading Variation
- Frost Resistance = Yes


[www.genrose.com](http://www.genrose.com)